HyPanel Elite 7 Datasheet

### Premium touch screen for your home

The akubela HyPanel Elite 7, with a Linux operating system, integrates smart intercom, ZigBee gateway and infrared remote control, provides audio and video communication with door phones via SIP 2.0 protocol. It delivers the ultimate touch screen experience in an unobtrusive, space-saving design featuring a brilliant 7-inch capacitive touch screen display.

#### At a Glance

- 7" touch screen with energy saving mode
- Two-way audio communication with other units in the network
- Smart home controller with ZigBee gateway and IR Control
- Powered by PoE or external source
- Support both US and EU electrical wall box mounting
- Support RS485



#### **Basic Information**

• Model Number: PG42

Power Supply: IEEE802.3af PoE & 12VDC

• Operation System: Linux

DDR/Flash: 128MB/256MB

• Wi-Fi: IEEE802.11 b/g/n/ax, @2.4GHz

• Ethernet Port: 2×RJ45, 10/100Mbps adaptive

• ZigBee: ZigBee 3.0

ZigBee Sub-Device Limit: 32

• RS485 Port: Supported

• Relay Output: 1 gang

0 - 30VDC, rated current: 2A

• Bell In Port: 1 channel

• Digital Input: 8 channels

• Microphone: Single microphone, -42dBV

• Speaker: Single speaker,  $4\Omega/2W$ 

• IR Control Coverage: Horizontal 90°, vertical 90°, 6m

## **Appearance**

• Material: V0 fireproof PC

• Screen: 7" touch screen

• Screen Resolution: 1024×600 pixels

• Screen Brightness: 300 cd/m²

## Working Environment

• Environment: For indoor use only

 Working Humidity: 10% ~ 90%RH, without condensation

Working Temperature: -10°C ~ 45°C

Storage Temperature: -20°C ~ 70°C

• IP Rating: IP20




**HyPanel Elite 7 Datasheet** 


## Installation


- Installation: Wall-mounted &Desktop
- Wall-mounted Standard: EU/UK/US standard


# Product Dimension Diagram (mm)



(5) BOTTOM VIEW







2 RIGHT VIEW

3 LEFT VIEW

(4) BACK VIEW



(6) TOP VIEW