New hassle-free smart control panel for your home

The akubela HyPanel KeyPlus, a smart control panel with an Android 13 operating system. The ALL IN ONE design integrates smart intercom, ZigBee gateway and home automation, and is compatible with plentiful ecosystem. Multi-modal interaction can be easily used by the whole family, offering the excellent smart home experience.

At a Glance

- Excellent performance with Android 13 system
- 4" multi-touch screen with energy saving mode
- 6 touch buttons, suitable for the whole family
- Built in with a 2-gang switch and a digital input port
- Smart intercom, ZigBee gateway, home automation ALL IN ONE
- EU standard flush mounted box;



Basic Information

• Model Number: KS53-KNX-EU

• KNX Power Supply: 21 ~ 30VDC

Rated Current: 12mA/21V

AUX Power Supply: 21 ~ 30VDC

Rated Current: 210mA/24V, 170mA/30V

Maximum Power Consumption: 5W

• Digital Input: 1 gang 0 - 5VDC

Dry Contact Output: 2 gang, 100 ~ 240VAC;

Rated Current: 4A;

Wire Range: $0.75 \sim 1.6 \text{mm}^2$ (18 $\sim 15 \text{AWG}$)

• Operation System: Android 13

• RAM/ROM: 2GB/8GB

• Wi-Fi: WiFi6, IEEE 802.11a/b/g/n/ac/ax

• Bluetooth: Bluetooth 5.3

• Ethernet Port: 1×RJ45, 10/100Mbps adaptive

• ZigBee: ZigBee 3.0

ZigBee Sub-Device Limit: 128

• Microphone: Dual microphones, -26dBFS

• Speaker: Single speaker, $8\Omega/1.5W$

Appearance

• Material: V0 fireproof PC

• Button: 6 touch button

• Screen: 4" multi-touch screen

• Screen Resolution: 480×480 pixels

Screen Brightness: 210 cd/m²

Sensors Built In

• Proximity Sensor: 30 ~ 60cm

• Light Sensor: Low-level lux detection



HyPanel KeyPlus Datasheet

Working Environment

• Environment: For indoor use only

 Working Humidity: 10% ~ 90%RH, without condensation

• Working Temperature: -10°C ~ 55°C

• Storage Temperature: -30°C ~ 70°C

• IP Rating: IP20

Product Dimension Diagram (mm)

Installation

• Installation: Wall flush mounting

• Flush Mounted Module: EU/UK standard

• Wiring Way: L- + N- wire required

