

Tonmind 30W IP Wall Speaker SIP-S11M



1. Two-way intercom communication.
2. IP 55 waterproof design for installation on exterior of building.
3. 48K OPUS Audio Codec enables excellent sound quality .
4. Compatible with VoIP, SIP devices (IPPBX, IP Phone) via SIP.
5. Compatible with IP Camera VMS via ONVIF.
6. Support Pre-recorded messages.
7. Support HPPT API for alarm in transmit.

Specification:

Audio

Decoding OPUS 48 kHz, MP3 44.1 kHz, G.722 ADPCM 16 kHz, G.711 PCMU 8 kHz, G.711 PCMA 8 kHz

Speaker

Max SPL	105dB
Frequency response	80Hz~20KHz
Frequency Range	500-2KHZ +-10dB 400-12KHZ +-20dB
Harmonic Distortion	0.1@1kHz
Signal to Noise Ratio	91dB

Network

Security:	Password protection, IP address filtering, Digest authentication, User access log, firewall
Network Protocol:	SIP, ONVIF, HTTP, IPv4, DHCP, RTSP, RTP, RTCP, TCP, UDP, ARP, FTP, TFTP, NFS, NTP
Network Interface:	10/100 Base-TX, RJ45
	Support for SIP protocol for intergration with VoIP systimes, intergrated with SIP/PBX.
VoIP:	Support SIP features: secondary/backend SIP server, IPv4 (IPv6 futhur)
	Support codecs: OPUS, G711U, G711A, GSM, MP3

Amplifier

Amplifier Description: Built-in 30W Amplifier

MIC

Built-in MIC Yes

General

Operating Temperature	'-30°C — +60°C
Operating humility	5%-85%
Material	ABS (IP55 water-proof)
Rate Power	30W
Power Supply	PoE or DC12V/24V
Installation	Wall Mounted
Dimensions	296 x 196 x 157 mm
Net Weight	2.5 KG
Languages	English
Warranty	2 years
Package Includes	Network Wall Speaker User Manual