

Tonmind 50W IP Ceiling Speaker SIP-S02

1. Transmit excellent sound for music and announcement.
2. PoE eliminates need for local power supply.
3. 48K OPUS Audio Codec enables excellent sound quality.
4. Compatible with VoIP, SIP devices (IPPBX, IP Phone) via SIP.
5. Compatible with IP Camera VMS via ONVIF.
6. Support Pre-recorded messages.
7. Support HPPT API for alarm in transmit.



Specification:

Audio

Codec OPUS 48 kHz, MP3 44.1 kHz, G.722 ADPCM 16 kHz, G.711 PCMU 8 kHz, G.711 PCMA 8 kHz

Speaker

SPL (1W/1M)	89dB
Frequency Response	80Hz ~ 20KHz
Frequency Range	500-2KHZ +-10dB 400-12KHZ +-20dB
Harmonic Distortion	0.1@1kHz
Impedance	8Ω

Network

Security	Password protection, IP address filtering, Digest authentication, User access log, firewall
Network Protocol	SIP, ONVIF, HTTP, IPv4, DHCP, RTSP, RTP, RTCP, TCP, UDP, ARP, FTP, TFTP, NFS, NTP
Network Interface	10/100 Base-TX, RJ45
	Support for SIP protocol for intergration with VoIP systems, intergrated with SIP/PBX.
VoIP	2 SIP Accounts, SIP Direct IP Call, RTP Multicast
	Codec: OPUS, MP3, G.722, PCMU, PCMA

Amplifier

Amplifier Description Built-in 50W Amplifier

General

Material	ABS
Rate Power	50W
Power Supply	PoE or DC 12V/24V
Installation	In Ceiling
Dimensions	Diameter 230 x 160 mm
Net Weight	1.9 KG
Languages	English
Warranty	2 years